

FRANKE FOODSERVICE SOLUTIONS

# EcO<sub>3</sub>Ice™

ANTIMICROBIAL ICE PROTECTION



Item #:
Project:
Quantity:

## MODEL NUMBER

X4

## PRODUCT OVERVIEW

The compact EcO3Ice™ device uses a unique, synthetic diamond-based technology that continuously treats incoming ingredient water used by ice machines, killing bacteria, yeast and mold in the ice-making path from beginning to end. Reduces biofilm build-up, greatly extending required time between cleanings. With each cycle, Eco3Ice™ creates a small, safe but effective amount of pure ozone—nature’s own sanitizer—which continuously treats the machine interior, storage bin, remote bin and drains.

## PRODUCT FEATURES

- Attaches quickly with no special tools to incoming water line of ice machine
- 3/8" push/pull quick connect fittings
- Runs silently and automatically
- Operator-replaceable, "twist-on" electrolytic cartridge
- LED indicator lamps show status, tell when it's time to replace cartridge

## X4 COMPATABILITY

- Fits most commercial ice machines with ice-making capacity of 100lbs/day or larger with flow rate of up to 1.3gpm
- For units requiring more than 1.3gpm, refer to Model X16

## CARTRIDGE LIFE

- 6 to 24 months
- Cartridge life is dependent upon water quality and ice machine water consumption

## WARRANTY

- Warranted against defects in materials and workmanship for 1 year, partonly, on head unit; 30 days parts-only on cartridge. Normal use exclusions apply, per Operating Manual.

ECO<sub>3</sub>ICE™ - ANTIMICROBIAL ICE PROTECTION



Approval \_\_\_\_\_


Franke Foodservice Solutions, Inc.  
 800 Aviation Parkway  
 Smyrna, TN 37167  
 Tel +1-877-379-3769  
 frankeamericas.com

*Make it wonderful*



# EcO<sub>3</sub>Ice™ - ANTIMICROBIAL ICE PROTECTION

## Model X4



<b>DIMENSIONS</b>	Width	3.8" 97mm
	Depth	3.6" 91mm
	Height	8.0" 203mm
<b>ELECTRICAL</b>	Voltage	100-240
	Phase	1
	Amps (by phase)	1.25 Max
	Watts (by phase)	240 Max
	Unswitched Circuit	 Within 5' of EcO <sub>3</sub> Ice assembly
<b>WEIGHT</b>	Net Weight	1.8 lbs
	Gross Weight	2 lbs
<b>SHIPPING</b>	FOB	Fayetteville, TN 37334
	Freight Class	Ships via UPS

**SHORT-FORM SPECIFICATIONS:** Model No EcO<sub>3</sub>Ice™ X4 measuring approximately 3.8" L x 3.6" W x 8.0" H(X4) and requiring 100-240v, 50/60 Hz supply for provided 24v, 1.25a transformer (integrated into power cord). Unit shall include synthetic diamond-based electrolytic technology to produce a small, safe and precise amount of dissolved ozone from the oxygen in the ice machine's water supply; removable electrolytic cell cartridge; LED indicator lights for cartridge replacement and system function. Shall include 1 year parts warranty on head unit and 30 days parts warranty on replacement cartridge.

<b>WATER</b>	Water Line Connection	3/8" OD push/pull fitting
	Water Temperature	40°F to 86°F (4°C to 30°C)
	Water Quality	Clean, Potable Water Only (recommended hardness ≤300 ppm CaCO <sub>3</sub> )
	Water Supply Pressure	*min 20 psi max 125 psi *min (1.37 bar) max (8.62 bar)
	Water Flow	0.34gpm - 1.3gpm (1.3lpm - 4.9lpm)
<b>MISC.</b>	1. Connect EcO <sub>3</sub> Ice™ only to a cube, not a flake/nugget, ice machine	
	2. Connect only one ice machine per EcO <sub>3</sub> Ice™ device	
	3. Connect EcO <sub>3</sub> Ice™ only to a commercial ice machine, not a household ice maker.	
	4. Do not connect EcO <sub>3</sub> Ice™ to other devices, such as a beverage or water dispenser.	
	5. EcO <sub>3</sub> Ice™ does not replace mechanical water filtration. For best results, always connect EcO <sub>3</sub> Ice™ in the water supply line between the filtration system and the ice machine.	

© 2016 Franke Foodservice Solutions, Inc. Due to continuous product development, Franke reserves the right to make changes in design and specifications without prior notice. Under license by Franke Technology and Trademark Ltd., Switzerland. Printed in USA.

*Make it Wonderful*

